

Model VFP191U 19" 1U Rack Mount Keyboard Display

BRIGHT SXGA DISPLAY
 USB/PS2 KEYBOARD WITH TOUCH PAD
 TEMPERED GLASS A/R PROTECTIVE WINDOW
 0° TO 50°C OPERATION
 ADJUSTABLE MOUNTING BRACKETS
 OPTIONAL 8 or 16 PORT KVM
 BUILT-IN THUMB SCREWS FOR LOCKDOWN
 INDUSTRIAL GRADE HEAVY DUTY STEEL CONSTRUCTION



Display Type:	19.0" TFT
Active Display Area:	15.21" (w) x 11.41" (h) (386.4 mm x 289.8 mm)
Pixel Pitch:	.294 mm
Brightness:	300 Nits
Viewing Angle:	Left/Right 80°/80° Up/Down 80°/80°
Contrast Ratio:	450:1 (Typical)
Response Time:	20 ms on/off
Display Colors:	16.7M
Input Signal:	Video: Analog 0.7V p-p/75 Ω Sync: Separate H&V
Input Interface:	HD-15
Video Inputs:	VGA-SXGA (HD-15)
Resolutions Supported:	640 x 480 800 x 600 1024 x 768 1280 x 1024
Native Resolution:	1280 x 1024 (SXGA)
Full Keyboard Options:	PS2 or USB Keyboard with Touch Pad

Temperature:	Operating:	0°C to 50°C
	Storage:	-20°C to 65°C
Humidity (Non-Condensing):	Operating:	10 to 80%
	Storage:	5 to 95%
Altitude:	Operating:	0 to 10,000 ft.
	Storage:	0 to 40,000 ft.
EMI:	FCC B	
Shock:	10g, 11ms, ½ Sine, 3 shocks/axis	
Vibration:	2g RMS, 14-500 Hz	
Power Requirements:	Voltage:	Internal 115/240 VAC @ 50/60 Hz
	Power:	30W
	Current:	.35A
	Standby Current:	.06A
Dimensions & Weight:	Height:	1.75" (44.45 mm)
	Width:	19.00" (482.6 mm)
	Depth:	21.6" (548.64 mm)
	Weight:	33 lbs (15 kg) w/o KVM
Agency:	Designed to meet FCC, RoHS, CE	
Optional KVM:	8 or 16 Port	
	Depth:	22.8" (580mm)
	Weight:	35 lbs (16 kg)



1 Riga Lane Birdsboro PA 19508 USA
 1-866-367-2934
 www.spartonre.com

All specifications subject to change without notice.