

MH70I

Rugged Industrial PC with Intel Core i3 / i5 / i7

Modular Built-to-Order Embedded Computer for Industrial Automation

- » Compact 40 HP application-ready system
- » Rack-mounted or wall-mounted
- » Fanless operation or forced-air cooling
- » Intel Core i7 or Celeron with standard HMI graphics
- » Up to 16 GB DDR3 DRAM soldered, ECC
- » Up to four SATA hard disks for a RAID
- » Single or redundant power supply (AC or DC)
- » 2 CompactPCI slots for fieldbus functions, RS232, analog I/O, digital I/O, Ethernet
- » 2 CompactPCI Serial slots for SATA RAIDs, Ethernet
- » 2 PCI or PCI Express slots for half-length cards
- » Pre-configured operating system and drivers



Modular, Built-to-Order Configuration

The MH70I is a modular application-ready industrial PC which meets the requirements of any industrial environment, e.g., control stations for industrial automation. The PC offers a multitude of configuration possibilities which are built to order resulting in a fast time-to-market. The system comes with complete software support.

The Intel Core i7-based system consists of a modular 40 HP CompactPCI system which can be wall or rack-mounted. The system can be cooled by natural convection or using an additional fan tray at the bottom of the system. Cooling is independent of the mounting position.

Redundant Power Supply

The pre-configured system offers two PSU slots to ensure reliability and redundancy. Normal operation is guaranteed if at least one external voltage is present. AC or DC power supplies can be implemented.

Large Range of Functions


Two CompactPCI peripheral slots and two CompactPCI Serial peripheral slots as well as 2 PCI or PCI Express slots can accommodate a large range of functions. If the 2 PCI or PCI Express slots are not required, two additional CompactPCI Serial peripheral slots are available.

Possible functions of the MH70I include binary and analog process I/O or motion counters as well as COMs and fieldbus functions such as CANopen, DeviceNet, Real-Time-Ethernet (EtherCAT, EtherNet/IP, Modbus, POWERLINK, PROFINET, SERCOS, Varan) and PROFIBUS (master and slave for all functions).

The system always offers 2 Gigabit Ethernet interfaces at the front of the CPU board. For extending the Ethernet functionality, there is the possibility to implement up to 8 additional standard RJ45 or fiber optics Ethernet interfaces in the Compact PCI Serial slots.

PCI Express Mini cards for wireless functions such as WLAN and UMTS can also be provided. A SATA RAID can be built using up to four CompactPCI Serial hard disk carrier boards.

The two PCI or PCI Express slots can be equipped with half-length cards for further customized extension of the system.



General System Characteristics

- Modular design, built-to-order configuration
- Slot and backplane set-up of the system
 - 2 PSU slots
 - 1 CompactPCI PlusIO system slot
 - 2 CompactPCI peripheral slots
 - 4 CompactPCI Serial peripheral slots
 - 2 PCI/PCIe slots
- [See the BTO configurator for component combination possibilities.](#)
- [Please contact MEN sales for more information.](#)

CPU Board

- CPCI 3U Board
- Configurable: yes
- Possible Configurations:
 - [Intel Celeron 1047UE 1.4 GHz, 2 GB DDR3 DRAM with ECC, -40°C to +85°C screened](#)
 - [Intel Core i7-3615QE, 2.3 GHz, 4 GB DDR3 DRAM with ECC, 0°C to +45°C](#)
- Mass Storage
 - [SSD mSATA 3.x, 64 GB, MLC, -40°C to +85°C](#)

Supervision and Control

- Dedicated shelf controller monitors power, CPU status, temperature; controls fan; provides status LEDs and power button
 - [More information on AF2 Shelf Controller for CompactPCI and CompactPCI Serial Systems](#)

Power Supply

- PSU 3U
- Configurable: yes
- Possible Configurations:
 - [120 W, 3U 6 HP PSU, wide range input 24 to 110 V DC, 24 V DC nom., output 12 V / 5 V / 3.3 V DC, -40..+85°C, qualified, conformal coating](#)
 - [120 W, 3U 6 HP PSU, wide range input 100 to 240 V AC, output 12 V / 5 V / 3.3 V DC, -40..+85°C, qualified, conformal coating](#)
- Two separate power inlet connectors
- Normal operation if at least one external voltage is present

Wireless Functionality via PCI Express Mini Cards

- CPCI 3U Board
- Configurable: yes
- Possible in CompactPCI peripheral slot: 3, 4
- 2 PCI Express Mini Card slots (USB), 4 SIM card sockets, 4 SMA connectors, -40..+85°C qualified (carrier only)
 - [More information on F212 PCI Express Mini Card carrier](#)
- Possible Configurations
 - [MC7304 PCI Express MiniCard, full-size on USB: LTE, DC-HSPA+, HSPA+, HSDPA, HSUPA, WCDMA, GSM, GPRS, EDGE, and GNSS, -40 to +85°C](#)

Serial I/O and CAN

- CPCI 3U Board
- Configurable: yes
- Possible in CompactPCI peripheral slots: 3 to 4
- 8 HP FPGA-based universal interface for direct connection of 2x CAN (first slot), 2x UART (second slot), -40..+85°C qualified
 - [More information on F215 Universal Interface Board](#)
- Possible Configurations
 - [RS232, not optically isolated, 0..+60°C](#)
 - [RS422/485, half duplex, optically isolated, 0..+60°C](#)
 - [RS422/485, full duplex, optically isolated, -40..+85°C screened](#)
 - [RS232, optically isolated, -40..+85°C screened](#)
 - [CAN bus ISO high-speed, optically isolated, -40..+85°C screened](#)

Serial I/O

- CPCI 3U Board
- Configurable: no
- Possible in CompactPCI peripheral slot: 3, 4
- 8 serial interfaces via 78-pin D-Sub, RS232/422/485 hardware-configurable, -40..+85°C qualified
 - [More information on F216 PCI Express Mini Card carrier](#)

Binary/Analog I/O and Motion Counters

- CPCI 3U Board
- Configurable: yes
- Possible in CompactPCI peripheral slot: 3, 4
- M-Module carrier board for 1 or 2 M-Modules, 0..+60°C
 - [More information on F204 M-Module carrier board for 1 M-Module](#)
 - [More information on F205 M-Module carrier board for 2 M-Modules](#)
- Possible Configurations
 - 16 analog voltage inputs, DC/DC converter, single-ended, -40..+85°C qualified
 - 8 analog voltage inputs, DC/DC converter, differential, -40..+85°C qualified
 - 16 analog current inputs, DC/DC converter, single-ended, -40..+85°C qualified
 - 8 analog current inputs, DC/DC converter, differential, -40..+85°C qualified
 - 4 analog current/voltage outputs, DC/DC converter, -40..+85°C qualified
 - 4 x 32-bit motion counter, 0..+60°C
 - 32 binary inputs and/or outputs, 0..+60°C

Industrial Field Bus by Hilscher

- CPCI 3U Board
- Configurable: yes
- Possible in CompactPCI peripheral slot: 3, 4
- Possible Configurations:
 - CANopen Slave interface, -20..+70°C screened
 - DeviceNet Slave interface, -20..+70°C screened
 - Real-Time-Ethernet Slave interface, supports Ethercat, Modbus, Powerlink, Profinet, Sercos, Varan, 0..+70°C screened
 - PROFIBUS DP Slave interface, -20..+70°C screened

Ethernet Interface Functionality

- CPCI Serial 3U Board
- Configurable: yes
- Possible in CompactPCI Serial peripheral slot: 6, 7
- Possible Configurations
 - 4 1000Base-T Ethernet interfaces, 4 RJ45 connectors at front, 0..+60°C
 - 4-channel 1000Base-SX Ethernet SerDes, 4 SFP slots, -40..+85°C screened

Mass Storage

- CPCI Serial 3U Board
- Configurable: yes
- Possible in CompactPCI Serial peripheral slot: 6, 7, 8, 9
- Possible Configurations
 - One 2.5" SATA HDD/SSD shuttle, hot swap, RAID 0, 1 support, -40..+85°C qualified (shuttle only)

2 PCI or PCI Express cards for customized functionality

- Half length PCI or PCI Express card
- Configurable: yes
- Possible in CompactPCI Serial peripheral slot: 8, 9
- Possible Configurations
 - Third-party PCI or PCI Express card

Mechanical Specifications

- Dimensions:
 - 210 x 175 x 225 mm max. without brackets
 - 4U, 40 HP
- Mounting Possibilities
 - Wall-mount
 - Rack-mount in 19" cabinet
 - Two systems side-by-side to build a single 19" chassis

Environmental Specifications

- Temperature range (operation): 0..+50°C according to EN 60068-2-1, EN 60068-2-2
- Temperature range (storage): -40..+85°C according to EN 60068-2-1, EN 60068-2-2
- Cooling concept
 - Air-cooled, forced convection with fan tray at system bottom
- Relative humidity (operation): according to EN 60068-2-30, non-condensing
- Relative humidity (storage): according to EN 60068-2-30
- Altitude: -300 m to +3000 m
- Shock: according to EN 61373 category 1 class B
- Vibration: according to EN 61373 category 1 class B
- International Protection Rating (IEC 60529): IP20

Safety

- Electrical Safety
 - EN 60950-1: Class I equipment
- Flammability (PCBs)
 - UL 94 V-0

EMC Conformity

- EN 55022 class B (radiated and conducted emissions)
- EN 55024 (immunity)

Software Support

- Windows Embedded Standard 7
- Linux
 - Ubuntu with current LTIB kernel

Germany

MEN Mikro Elektronik GmbH

Neuwieder Straße 3-7
90411 Nuremberg
Phone +49-911-99 33 5-0

sales@men.de
www.men.de

USA

MEN Micro Inc.

860 Penllyn Blue Bell Pike
Blue Bell, PA 19422
Phone 215-542-9575

sales@menmicro.com
www.menmicro.com

France

MEN Mikro Elektronik SAS

18, rue René Cassin
ZA de la Châtelaine
74240 Gaillard
Phone +33-450-955-312

sales@men-france.fr
www.men-france.fr

China

MEN Mikro Elektronik Co., Ltd.

Room 301A, #971 Dongfang Road
200122 Shanghai
Phone +86-21-5058-0963

sales@men-china.cn
www.men-china.cn

Up-to-date information, documentation and ordering information:

www.men.de/products/mh70i/

MEN is not responsible for the results of any actions taken on the basis of information in the publication, nor for any error in or omission from the publication. MEN expressly disclaims all and any liability and responsibility to any person, whether a reader of the publication or not, in respect of anything, and of the consequences of anything, done or omitted to be done by any such person in reliance, whether wholly or partially, on the whole or any part of the contents of the publication.

The correct function of MEN products in mission-critical and life-critical applications is limited to the environmental specification given for each product in the technical user manual. The correct function of MEN products under extended environmental conditions is limited to the individual requirement specification and subsequent validation documents for each product for the applicable use case and has to be agreed upon in writing by MEN and the customer. Should the customer purchase or use MEN products for any unintended or unauthorized application, the customer shall indemnify and hold MEN and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim or personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that MEN was negligent regarding the design or manufacture of the part.

In no case is MEN liable for the correct function of the technical installation where MEN products are a part of.

© 2018 MEN Mikro Elektronik GmbH