

IC-INT-VPX6d

Dual Intel® XEON SBC (Broadwell-DE SoC)

The new VPX 6U Digital Signal Processor (DSP) board **IC-INT-VPX6d** is the result of the experience and expertise gained by Interface Concept in the High Performance Embedded Computing (HPEC) field.

Taking advantages of the latest Intel's 14nm Xeon enhancements and the intercommunication capabilities provided by the OpenVPX standard, the **IC-INT-VPX6d** is the current most comprehensive dual Intel® processor design for applications requiring the highest processing capabilities together with "controlled" power consumption.

As an Interface Concept trademark, the optional on-board Xilinx® FPGA is a real plus for users looking for an open and flexible SBC. In the same spirit, IC offers the users with its own boot loader the security of always being able to support them as expected.

OpenVPX



Description

The two computing nodes (A & B) are populated with XEON-D processors implementing up to twelve cores.

For Data Plane and Expansion Plane, The **IC-INT-VPX6d** implements one PCIe Gen2/Gen3 switch attached to both CPUs via x8 links and to the backplane through 16 lanes (**4 x4** or **2 x8**) on P1 and, optionally, 12 lanes (**4 x4** or **2 x8**) on P2. Optimized features of this PCIe switch (such as virtualization) allow versatile PCIe backplane configurations.

Moreover, the two processors are linked together via a PCIe x4 link.

For Control Plane, the **IC-INT-VPX6d** implements an ultra low latency GE switch attached to each CPU and offering seven GigE ports (two of them capable of handling 2.5 Gbps). Moreover, one rear 10GigaE port is connected directly to each processor (10G KR).

An XMC site is attached to Node A (PCIe X4 / optional attachment to Node B PCIe X1 for custom application) and provides 20 differential I/O pairs routed from Pn6 to P6 in accordance with X12d+X8d pattern of VITA 46.9 and 9 single ended IO to P5/P6.

The **IC-INT-VPX6d** also takes advantage of the capabilities of this SoC solution to provide GPIOs, two USB and one SATA ports per processor. For storage, the board also features soldered SATA NAND SSD.

The **IC-INT-VPX6d** implements one FPGA interfaced with Node A (PCIe x4) to add Core Functions, for which IC provides a variety of IPs. This FPGA is connected directly to the P3/P4 connectors (SERDES/GPIOs).

Note: this board is compatible with our previous versions of Intel® Core™ i7 (Gen 2 & 3) SBC to allow customers to upgrade existing systems and/or maintain existing design for long term support.

Main features

Processor Unit (per processor)

- ▶ Xeon D-15xx
- ▶ DDR4 with ECC (up to 32GB)
- ▶ boot flash memory
- ▶ on board SATA SSD (up to 64GB)
- ▶ TPM 2.0

Communication subsystem (per processor)

- ▶ 1 * PCIe x8 to PCIe switch
- ▶ 1 * PCIe x4 to second processor
- ▶ 2 * USB ports (2 rear)
- ▶ 1 * Console port
- ▶ 2 * rear SATA interfaces
- ▶ GPIOs (Rear)
- ▶ 1 * GigE port (attached to the switch)
- ▶ 1 * 10G-KR (rear)

Ethernet Switch

- ▶ 7 * GigE ports (rear: 2 * 1000Base-T and 5 * 1000Base-BX)

Extension (Node A)

- ▶ 1 * XMC slot (PCIe x4)
- ▶ 20 differential pairs (from Pn6 to P6 - X12d+X8d)

FPGA (Node A)

- ▶ 1 * FPGA Kintex-7 160T
- ▶ MGT x4 (to P4)
- ▶ 16 differential pairs (to P3)

Miscellaneous

- ▶ PIC μ-controller for System Management (per VITA 46.11)
- ▶ Power supply monitoring / Temperature sensor...
- ▶ Status LEDs
- ▶ Engineering kit for debug: JTAG/COP...
- ▶ 6U Rear Transition Module

The **IC-INT-VPX6d** is a 6U x 5HP (1") VPX board compliant with 6U module definitions of the VITA 46.0 standard (0.80 or 0.85" : please consult us), available in air-cooled and conduction cooled (without any front I/O) versions.

IC-INT-VPX6d

Dual Intel® XEON SBC (Broadwell-DE)

On-board firmware

Interface Concept Single Board Computers based on Intel CPUs, use the new UEFI firmware technology. This Boot Loader, **developed and tested by our R&D team**, implements all the initializations and optimized PBITs while ensuring the shortest boot time before launching the UEFI shell or loading the Operating System from storage devices (CD, DVD, HDD, USB...) or network.

When the final application is running, Runtime services remain in memory thus allowing the user to access UEFI variables for monitoring (e.g. PBIT results) or setup operations.

On request, we can customize the Boot Loader to keep only what is strictly necessary for customer's applications.

OS support


Interface Concept provides LSP Linux® distributions (IC SDK, others...) and VxWorks® 7.0.

Multware

In order to empower customers to concentrate their efforts on their most critical tasks, Interface Concept has developed a Fabric Management Software implementing optimized services between PCIe domains over non transparent bridges (NTB) such as: DMA transfers, Ethernet emulation over PCIe, management of shared memory, messages and semaphores, etc.

(please consult us for details)

Block Diagram



Environmental Specifications:

Please consult the IC-INT-VPX6d page at www.interfaceconcept.com.

Ordering Information:

Please contact our sales department : tel. +33 (0)2 98 573 030 - email : info@interfaceconcept.com

This document supersedes any earlier documentation relating to the products referred to herein. The information contained in this document is current at the date of publication. It may subsequently be updated or withdrawn without notice.

